

Kirk Sandall Industrial Estate, Doncaster, South Yorkshire, DN3 1QR

+44 (0)1302 310 113 enquiries@prosolveproducts.com www. prosolveproducts.com

ProSolve<sup>®</sup> is a registered trademark of S.T.L Trading Company Limited Reg in England No: 5230722 VAT Reg No: 381 3533 58

# **DATA SHEET**

ProSolve Cross Weave Tape (CWT50 and CWT75)

## **Product Description**

A super strong reinforced tape with glass fibre running along the length and width of the roll. This unbreakable tape is used for box sealing, bundling and binding.

### Features

- Backed with polyester film
- Reinforced with Glass Fibres
- Coated with Rubber Adhesive for Strong Adhesion
- High Tack and Peel.
- High Resistance to Abrasion
- Impact-Resistance
- Superior Holding Power

#### **Physical Properties:**

Backing:	Backed with PET film, Reinforced with Bi-Way woven Glass Fibres.
Adhesive:	Synthetic Rubber Resin
Total Thickness:	140μm ±10μm
Tensile Strength:	400 N/25mm
Elongation at break:	12%
Adhesion To Steel:	18 N/25mm
Holding Power:	>24h
Service Temperature	: -5°C to 70°C
Sizes:	50 and 75mm
Inner core diameter:	76 mm

#### **IMPORTANT NOTICE**

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT.