Kirk Sandall Industrial Estate, Doncaster, South Yorkshire, DN3 1QR

+44 (0)1302 310 113
enquiries@prosolveproducts.com
www. prosolveproducts.com

ProSolve® is a registered trademark of S.T.L Trading Company Limited
Reg in England No: 5230722
VAT Reg No: 381 3533 58

ProSolve Graphited Penetrating Oil - Technical Data Sheet

Product Code: GPO5

Pack Size: 500ml Aerosol

Product Description

ProSolve Graphited Penetrating Oil is designed to efficiently and rapidly free and loosen seized nuts, bolts, hinges and other mechanical components. It is a high-performance multi-function fluid incorporating graphite to improve and enhance lubrication and durability. The product offers long lasting lubricant and anti-corrosion protection, with a high-tack formulation designed to penetrate, lubricate, release and protect.

Applications

Seized nuts, bolts, hinges and fixings

DIY, workshop, garage and maintenance applications

Motorcycle maintenance

Automotive and general lubrication tasks

Freeing and loosening seized mechanical components

Moisture repellent and corrosion protection applications

Features & Benefits

High-tack penetrating oil

Helps free seized components

Graphited formulation enhances lubrication and durability

Penetrates, lubricates and releases

Helps protect against corrosion

Helps prevent lubricant throw-off

Provides maximum protection

Aerosol format for easy application

Directions for Use

Shake well before use. If using for moisture repellent purposes, spray from a distance of approximately 20-30cm onto the surface and leave for a moment before continuing to work. If using as a protective coating, spray onto the surface and allow to dry to give a protective film. Use only in a well-ventilated area and avoid breathing vapour or spray mist.

Composition Information

Contains hydrotreated light naphtha, hydrocarbons, propane, butane, isobutane and propan-2-ol. Contains graphite as part of the lubricating formulation.

Typical Technical Data

Appearance: Aerosol

Colour: Grey

Odour: Characteristic odour

Flash Point: -60°C

Solubility: Not specified on supplied SDS

Formulation Type: Graphited penetrating lubricant aerosol

Propellant: Hydrocarbon propellant blend

Transport Classification: UN1950 Aerosols, Class 2

Storage

Store in a cool, well-ventilated area. Keep container tightly closed and in the original packaging. Keep away from direct sunlight and sources of ignition. Do not expose to temperatures exceeding 50°C. Store away from heat, hot surfaces, sparks, open flames and other ignition sources.

Limitations

Use only as directed. Do not spray onto naked flames or other ignition sources. Do not pierce or burn the container, even after use. Avoid use on surfaces where a lubricating film would create a slip hazard or interfere with subsequent painting, bonding or finishing operations unless compatibility has been checked first.

Health & Safety

Extremely flammable aerosol. Pressurised container may burst if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. Toxic to aquatic life with long lasting effects. Use only in well-ventilated areas and wear suitable protective equipment where required. Always read the product label and Safety Data Sheet before use.

Packaging

500ml aerosol can

Product Code: GPO5

Company Information

ProSolve

Sandall Stones Road

Kirk Sandall Industrial Estate

Doncaster

South Yorkshire

DN3 1QR

Tel: +44 (0)1302 310 113

Email: enquiries@prosolveproducts.com

Website: www.prosolveproducts.com

Disclaimer

The information contained within this document is believed to be accurate at the time of publication and is provided for guidance purposes only. Users should satisfy themselves that the product is suitable for their intended application. Consult the Safety Data Sheet prior to use.