Kirk Sandall Industrial Estate, Doncaster, South Yorkshire, DN3 1QR

+44 (0)1302 310 113
enquiries@prosolveproducts.com
www. prosolveproducts.com

ProSolve® is a registered trademark of S.T.L Trading Company Limited
Reg in England No: 5230722
VAT Reg No: 381 3533 58

DATA SHEET

ProSolve PTFE Graphited Dry Film Lube - Technical Data Sheet

Product Code: PTFEG5
Pack Size: 500ml Aerosol

Product Description

ProSolve PTFE Graphited Dry Film Lube is a specially formulated dry film lubricant designed to provide long-lasting lubrication and protection while reducing friction. The product leaves a durable dry film coating and is suitable for light-duty lubrication where surfaces slide together or where products slip over a surface. It can also function as a release agent in environments such as printing and chemical industries.

Applications

- Sliding surfaces
- Light-duty lubrication
- Release agent applications
- Printing industry applications
- Chemical industry applications
- Maintenance and assembly work
- Components where a dry lubricating film is required

Features & Benefits

- Lubricates and protects
- Penetrates working surfaces
- Anti-static properties
- Silicone-free formulation
- Reduces friction
- Leaves a long-lasting dry film coating
- Can be used as a release agent

Directions for Use

Shake well before use. Spray a light, gentle coating over the surface from a distance of approximately 15-20cm. Multiple coats may improve coverage. Initially, a light dust coating will be seen with the more durable film beneath.

Typical Technical Data

Appearance: Liquid aerosol

Colour: Black

Odour: Solvents

Flash Point: <23°C

Flammability: Extremely flammable aerosol

Base: PTFE graphited dry film lubricant

Application Distance: 15-20cm

Composition Information
Contains acetone, liquefied petroleum gases, 1-methoxy-2-propanol, 2-butoxyethanol and alkanes C14-17, chloro. The formulation contains PTFE and graphite to provide dry film lubrication and release performance.

Storage
Store in a cool, well-ventilated place. Keep container tightly closed. Protect from direct sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat, sparks, open flames and other ignition sources.

Limitations
Use only in well-ventilated areas. Avoid contact with skin and eyes. Do not breathe vapours or spray mist. Avoid release into the environment. Do not spray onto naked flames, hot surfaces or other ignition sources.

Health & Safety
Extremely flammable aerosol. Pressurised container may burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. May cause harm to breast-fed children. Harmful to aquatic life with long-lasting effects. Always read the product label and Safety Data Sheet before use.

Packaging
500ml aerosol can

Product Code: PTFEG5

Company Information
ProSolve

Sandall Stones Road

Kirk Sandall Industrial Estate

Doncaster

South Yorkshire

DN3 1QR

Tel: +44 (0)1302 310 113

Email: enquiries@prosolveproducts.com

Website: www.prosolveproducts.com

Disclaimer
The information contained within this document is believed to be accurate at the time of publication and is provided for guidance purposes only. Users should satisfy themselves that the product is suitable for their intended application. Consult the Safety Data Sheet prior to use.

IMPORTANT NOTICE

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

Consult the Safety Data Sheet prior to use.