



Kirk Sandall Industrial Estate, Doncaster, South
Yorkshire, DN3 1QR

+44 (0)1302 310 113
enquiries@prosolveproducts.com
www. prosolveproducts.com

ProSolve® is a registered trademark of S.T.L Trading
Company Limited
Reg in England No: 5230722
VAT Reg No: 381 3533 58

DATA SHEET

ProSolve Single Sided DPM Jointing Tape (PVSSJT50 and PVSSJT75)

Product Description

An ultra strong bi-directional filament tape that is ideal for jointing damp proof membranes, gas barriers and all plastic sheeting.

Features

- Backed with polyester film
- Reinforced with Glass Fibres
- Coated with Rubber Adhesive for Strong Adhesion
- High Tack and Peel.
- High Resistance to Abrasion
- Impact-Resistance
- Superior Holding Power

Physical Properties:

Backing: Backed with PET film, Reinforced with Bi-Way woven Glass Fibres.

Adhesive: Synthetic Rubber Resin

Total Thickness: 140µm ±10µm

Tensile Strength: 400 N/25mm

Elongation at break: 12%

Adhesion To Steel: 18 N/25mm

Holding Power: >24h

Service Temperature: -5°C to 70°C

Sizes: 50 and 75mm

Inner core diameter: 76 mm

IMPORTANT NOTICE

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT.