



Kirk Sandall Industrial Estate,
Doncaster, South Yorkshire, DN3 1QR


+44 (0)1302 310 113
enquiries@prosolveproducts.com
www.prosolveproducts.com

ProSolve is trademark of S.T.L Trading
Company Limited
Reg in England No: 5230722
VAT Reg No: 381 3533 58

Technical Data Sheet – Premium Super Strong Barrier Fencing

Product Description

- Extruded High Density Polyethylene (HDPE)
- UV Stabilised
- Colour: Various
- Shape: Rectangle



Technical details

Properties	Value	Unit	Test Method
Tensile Strength (MD)	2.50	kN/m	EN ISO 10319
Tensile Strength (CD)	0.55	kN/m	EN ISO 10319
Thickness	0.65 (± 0.1)	mm	EN ISO 9863-1
Weight / GSM	80 gm/m ² (+/-5gm)	gram	EN ISO 9864
Mesh Size	100 x 40 (± 1 mm)	mm	Scale
Roll Width	1	meter	Scale
Roll Length	50	meter	Scale

We recommend that fencing pins be used every 5m.

NOTE: This product is not fire resistant and isn't designed to resist heat.

IMPORTANT NOTICE

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT.