



Kirk Sandall Industrial Estate,
Doncaster, South Yorkshire, DN3
1QR

+44 (0)1302 310 113
enquiries@prosolveproducts.com
www.prosolveproducts.com

ProSolve is trademark of S.T.L
Trading Company Limited
Reg in England No: 5230722
VAT Reg No: 381 3533 58

TECHNICAL DATA SHEET

ProSolve Pipe Jointing Lubricant 2.5kg

Code: PVPL2.5

Product Description

Concrete Pipes: Pipe Jointing Lube is ecologically friendly biodegradable blend of vegetable-based oil and is used to facilitate the easy jointing of concrete, clay and plastic pipes. Pipe Jointing Lube can be applied as a soft gel that is ready for direct application to the concrete surface, whether wet or dry.

Masking Gel: Pipe Jointing Lube can also be used as water-based masking Gel that can be used for masking the walls, floors and fittings in spray booths. The coating can be easily washed away with water, without the need for solvents.

Applications

Concrete Pipes: Pipe Jointing Lube is used to lubricate concrete pipes, plastic or other sealing rings. It is miscible in water allowing it to be used in wet weather on site; it can also be used in wet and dry pipe jointing processes. The Pipe Jointing Lube can also be used as environmentally friendly concrete release lubricant.

Masking Gel: Pipe Jointing Lube use as supplied and apply as a thick paste with a brush or a roller. The viscous paste can be removed with a jet of water or simply scraped off.

Benefits

- Biodegradable
- Excellent at low temperatures
- Miscible in water

Properties

Nature:	Soft Gel
Colour:	White
Specific Gravity:	0.96 g/cm ³
pH:	-
Chloride Content:	-
Application Temp:	-20C to 40C

Instructions for use

Ensure that the concrete and surrounding areas are clean and free of contamination before the application of Pipe Jointing Lube. Apply Pipe Jointing Lube around the entire circumference of the spigot and to the seal. Apply by brush, trowel sponge or gloved hand, to the desired area. Re-apply to the spigot if the Pipe Jointing Lube becomes contaminated.

Pipe Jointing Lube is compatible with most 'O' ring, gasket materials such as EPDM and neoprene.

Cleaning & Disposal

Equipment can be cleaned with detergent and warm, soapy water. Pipe Jointing Lube is a non-hazardous product but in line with normal handling procedures, personal protective equipment should be worn. Refer to the Material Safety Data Sheet for full details.

Storage

Store unopened within the range 5°C - 30°C will have a minimum shelf life of 12 months.

Always re-seal the container after use.

IMPORTANT NOTICE

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to

herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT.